


 mm inch			 A	 B	 C				
6,35 1/4 P	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5203 750 7017	R = 1,7 mm α = 30°	0000 893 4005 b = 0,45 mm (0.018")	75°	
					5203 750 7015				
6,35 1/4 9,32 3/8 P	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5203 750 7013	R = 2,0 mm α = 30°	1110 893 4000 b = 0,65 mm (0.025")	PS...: 60° PM...: 75°	
					5203 750 7015				
9,32 3/8 P PMN	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5203 750 7013	R = 2,0 mm α = 30°	1110 893 4000 b = 0,65 mm (0.025")	75°	
					5203 750 7015				
8,25 0.325	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5203 750 7010	R = 2,4 mm α = 30°	1110 893 4000 b = 0,65 mm (0.025")	RS...: 60° RM...: 75°	
					5203 750 7015				
9,32 3/8	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5203 750 7010	R = 2,6 mm α = 30°	1110 893 4000 b = 0,65 mm (0.025")	RS...: 60° RM...: 75°	
					5203 750 7015				
10,26 0.404	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5202 750 7010	R = 2,8 mm α = 30°	1106 893 4000 b = 0,80 mm (0.030")	RS...: 60° RM...: 75°	
					5203 750 7015				
9,32 3/8 P PMX 	① / ② ③	+40° / +40° +40°	-15 / +15 0	-10° / +10° 0°	5203 750 7013	R = 2,0 mm α = 30°	1110 893 4000 b = 0,65 mm (0.025")	75°	
					5203 750 7015				
9,32 3/8 RMX 	① / ② ③	+40° / +40° +40°	-15 / +15 0	-10° / +10° 0°	5203 750 7010	R = 2,6 mm α = 30°	1110 893 4000 b = 0,65 mm (0.025")	75°	
					5203 750 7015				
10,26 0.404 RCX / RMX 	① / ② ③	+40° / +40° +40°	-15 / +15 0	-10° / +10° 0°	5202 750 7010	R = 2,8 mm α = 30°	1106 893 4000 b = 0,80 mm (0.030")	75°	
					5203 750 7015				
10,26 0.404 RMH 	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5202 750 7010	R = 2,8 mm α = 30°	1106 893 4000 b = 1,50 mm (0.060")	75°	
					5203 750 7015				
10,26 0.404 RMHS 	① / ② ③	+40° / +40° +40°	-15 / +15 0	-30° / +30° 0°	5202 750 7010	R = 2,8 mm α = 30°	1106 893 4000 b = 1,00 mm (0.040")	75°	
					5203 750 7015				
9,32 3/8 P PD3	① / ② ③	+30° / +30° +40°	-15 / +15 0	-30° / +30° 0°	5203 750 0906	- α = 30°	1110 893 4000 b = 0,65 mm (0.025")	75°	
					5203 750 7015				
8,25 0.325 9,32 3/8 RD3	① / ② ③	+30° / +30° +40°	-15 / +15 0	-30° / +30° 0°	5203 750 0906	- α = 30°	1110 893 4000 b = 0,65 mm (0.025")	75°	
					5203 750 7015				
9,32 3/8 RD	① / ② ③	+20° / +20° +40°	0 / 0 0	-25° / +25° 0°	5203 757 0901	- α = 30°	1110 893 4000 b = 0,65 mm (0.025")	65°	
					5203 750 7015				
9,32 3/8 RDR	① / ② ③	+10° / +10° +40°	0 / 0 0	-15° / 15° 0°	5203 757 0901	- α = 30°	1110 893 4000 b = 0,65 mm (0.025")	85°	
					5203 750 7015				
9,32 3/8 RH	① / ② ③	+25° / +25° +40°	0 / 0 0	-25° / +25° 0°	5203 750 7018	- α = 30°	1110 893 4000 b = 0,65 mm (0.025")	60°	
					5203 750 7015				


STIHL USG



STIHL®

		A	B	C		
4232	HL 45	- 10°	0	+ 45° / - 45°	5203 750 7010	R = 2,4 mm
4230	HL 75, HLR 85	- 10°		+ 45° / - 45°		
4236	HL 56	- 10°		+ 45° / - 45°		
4243	HL 91, 92, 94, 111	- 10°		+ 45° / - 45°		
4280	HL 100, 90 K	- 10°		+ 45° / - 45°		
4859	HLA 65, 66, 85, 86	- 10°		+ 45° / - 45°		
HA01	HLA 56	- 8°		+ 55° / - 55°		
HA04	HLA 135	- 10°		+ 45° / - 45°		
4813	HLE 71	- 10°		+ 45° / - 45°		
4228	HS 45	- 6°		+ 55° / - 55°		
	HS 52	-10°		+ 45° / - 45°		
4242	HS 56	- 10°		+ 45° / - 45°		
	HS 46	- 10°		+ 55° / - 55°		
4211	HS 61	- 10°		+ 45° / - 45°		
4226	HS 75, 80, 85	- 10°		+ 45° / - 45°		
4237	HS 81, 86	- 10°		+ 45° / - 45°		
	HS 82, 87	- 10°		+ 45° / - 45°		
4213	HS 246	- 10°		+ 45° / - 45°		
4521	HSA 56,	- 8°		+ 55° / - 55°		
	HSA 56 (USA/CDN)	- 8°		+ 50° / - 50°		
4851	HSA 65,	- 8°	+ 48° / - 48°			
	HSA 65 (USA/CDN)	- 8°	+ 50° / - 50°			
	HSA 66,	- 8°	+ 55° / - 55°			
	HSA 66 (USA/CDN)	- 8°	+ 50° / - 50°			
	HSA 85, 86	- 10°	+ 45° / - 45°			
4869	HSA 94	- 10°	+ 45° / - 45°			
4812	HSE 60, 70	- 8°	+ 51° / - 51°			
	HSE 61	- 8°	+ 55° / - 55°			
	HSE 71	- 8°	+ 62° / - 62°			
	HSE 81	- 10°	+ 45° / - 45°			
4818	HSE 42,	- 8°	+ 54° / - 54°			
	HSE 52	- 8°	+ 58° / - 58°			

STIHL USG



		A	C			
	+ 5° ... + 15° hard ... soft		+ 15° / - 15°	5203 750 7010	R = 2,4 mm	
	+ 5° ... + 15° hard ... soft		+ 15° / - 15°			
	0°		0°			
	7°		+ 5° / - 5°			5203 757 0901